
















BELLOWS STYLE

GOODYEAR PART NO.	Side View With Extended and Compressed Height	Upper Mounting View	Lower Mounting View	Replaces These Springs
2B14-367 Flexmember 578-92-3-353		ASA-92-8-049 	ASA-92-6-043 	Dayton 354-7123 Triangle 4345 Firestone 7123 7133 KwikLok/Todco (Jifflox) 53671 Load Guard SC2080 Navistar 1685184C1
2B14-383 Flexmember 578-92-3-356		ASA-92-8-174 	ASA-92-6-118 	Firestone 7557 Reyco 19983-01 Triangle 4530 Watson & Chalin AS-0089
2B14-462 Flexmember 578-92-3-356		ASA-92-8-030 	ASA-92-6-013 	Firestone 6805 Ridewell 1003586805C
2B14-469 Flexmember 556-23-8-329		ASA-92-8-352 	ASA-92-6-016 	Neway 90557257
2B14-470 Flexmember 578-92-3-356		ASA-92-8-031 	ASA-92-6-015 	Firestone 7782 Triangle 4544

- - Bolt or Stud - 1/2-13 or 1/2-20
- ⊗ - Air Fitting - 1/4 NPTF
- ⊙ - Stud - 3/4-10
- ⊕ - Tapped Hole on Top Retainers
- ⊗ - Air Fitting - 1/2 NPTF
- ⊗ - Combination Stud Air Fitting
- 3/8-16, on Pistons - 1/2-13
- 3/8 NPTF
- Stud - 3/4-16; Air Fitting - 1/4 NPTF