

# BELLOWS STYLE

GOODYEAR PART NO.	Side View With Extended and Compressed Height	Upper Mounting View	Lower Mounting View	Replaces These Springs
<b>2B9-244</b>  Flexmember 578-92-3-202		<b>ASA-92-8-172</b> 	<b>ASA-92-6-044</b> 	<b>Firestone</b> 6941
<b>2B9-245</b>  Flexmember 578-92-3-202		<b>ASA-92-8-113</b> 	<b>ASA-92-6-108</b> 	<b>Firestone</b> 7788 <b>Triangle</b> 4510
<b>2B9-246</b>  Flexmember 578-92-3-211		<b>ASA-92-8-172</b> 	<b>ASA-92-6-108</b> 	<b>Firestone</b> 6932 <b>Ridewell</b> 1003586932C <b>Triangle</b> 4452
<b>2B9-250</b>  Flexmember 578-92-3-206		<b>AS1-92-8-040</b> 	<b>ASA-92-6-010</b> 	<b>Firestone</b> 6943 <b>Load Guard</b> SC2112 <b>Suspensions, Inc.</b> 200835 <b>Triangle</b> 4426 <b>Watson &amp; Chalin</b> AS-0041
<b>2B9-251</b>  Flexmember 578-92-3-206		<b>AS1-92-8-040</b> 	<b>ASA-92-6-010</b> 	<b>Firestone</b> 6948 <b>Load Guard</b> SC2123 <b>Ridewell</b> 1003586948C <b>Triangle</b> 4429

- - Bolt or Stud - 1/2-13 or 1/2-20
- ⊗ - Air Fitting - 1/4 NPTF
- ⊙ - Stud - 3/4-10
- ⊕ - Tapped Hole on Top Retainers
- ⊗ - Air Fitting - 1/2 NPTF
- ⊗ - Combination Stud Air Fitting
- 3/8-16, on Pistons - 1/2-13
- 3/8 NPTF
- Stud - 3/4-16; Air Fitting - 1/4 NPTF