
















BELLOWS STYLE

GOODYEAR PART NO.	Side View With Extended and Compressed Height	Upper Mounting View	Lower Mounting View	Replaces These Springs
2B9-244 Flexmember 578-92-3-202		ASA-92-8-172 	ASA-92-6-044 	Firestone 6941
2B9-245 Flexmember 578-92-3-202		ASA-92-8-113 	ASA-92-6-108 	Firestone 7788 Triangle 4510
2B9-246 Flexmember 578-92-3-211		ASA-92-8-172 	ASA-92-6-108 	Firestone 6932 Ridewell 1003586932C Triangle 4452
2B9-250 Flexmember 578-92-3-206		AS1-92-8-040 	ASA-92-6-010 	Firestone 6943 Load Guard SC2112 Suspensions, Inc. 200835 Triangle 4426 Watson & Chalin AS-0041
2B9-251 Flexmember 578-92-3-206		AS1-92-8-040 	ASA-92-6-010 	Firestone 6948 Load Guard SC2123 Ridewell 1003586948C Triangle 4429

- - Bolt or Stud - 1/2-13 or 1/2-20
- ⊗ - Air Fitting - 1/4 NPTF
- ⊙ - Stud - 3/4-10
- ⊕ - Tapped Hole on Top Retainers
- ⊗ - Air Fitting - 1/2 NPTF
- ⊙ - Combination Stud Air Fitting
- ⊕ - Air Fitting - 3/8-16, on Pistons - 1/2-13
- ⊗ - 3/8 NPTF
- ⊙ - Stud - 3/4-16; Air Fitting - 1/4 NPTF