
















BELLOWS STYLE

GOODYEAR PART NO.	Side View With Extended and Compressed Height	Upper Mounting View	Lower Mounting View	Replaces These Springs
2B9-266 Flexmember 578-92-3-208		ASA-92-8-292 	ASA-92-6-044 	Firestone 6944 Triangle 4454
2B9-270 Flexmember 578-92-3-206		ASA-92-8-298 	ASA-92-6-010 	Ridewell 1002B09270G
2B10-226 Flexmember 578-92-3-250		AS1-92-8-113 	ASA-92-6-010 	Firestone 7795 Hendrickson B14486 Triangle 4524
2B12-300 Flexmember 578-92-3-309		ASA-92-8-003 	ASA-92-6-001 	Dayton 354-7424 Firestone 7424 HDA PMABG-7424B Load Guard SC2024 Navistar 554785C1 Neway TC-144-2 90557014 R&S Truck 1090215 Porcupine Sauer Axles P10-755 Taurus AS214-7424 Triangle 4327 Watson&Chal n AS-0009
2B12-305 Flexmember 578-92-3-310		AS1-92-8-026 	AS1-92-6-002 	Dayton 354-7443 Firestone 7443 Granning 1218 1589 Load Guard SC2026 Navistar 554786C1 Ridewell S-2683C Triangle 4323 Watson&Chal n AS-0027

● - Bolt or Stud - 1/2-13 or 1/2-20
 ⊕ - Tapped Hole on Top Retainers
 3/8-16, on Pistons - 1/2-13

⊗ - Air Fitting - 1/4 NPTF
 ⊗ - Air Fitting - 1/2 NPTF
 3/8 NPTF

○ - Stud - 3/4-10
 ⊗ - Combination Stud Air Fitting
 Stud - 3/4-16; Air Fitting - 1/4 NPTF